



## TECHNICAL SPECIFICATIONS

### STORAGE RECOMMENDATIONS:

The recommended storage time and use of the stoppers is of 6 months since the manufacturing date. Storage should be under original packaging. Avoid the cork stoppers from coming into contact with chemical products, pesticides, fungicides, chlorine-based sanitary products and treated wooden structures (in particular PCP- Pentachloropheno's). Do not store directly on the floor. Do not expose to sunlight, even through glass. In case of any doubt or comments please do not hesitate to contact us at [trefinos@trefinos.es](mailto:trefinos@trefinos.es)



CHARACTERISTICS		VALUES		SPECIFICATION	METHODOLOGY
DIMENSIONAL	LENGTH	Nom. value	mm	± 0,5	UNE 56933
	DIAMETER	Nom. value	mm	± 0,3	UNE 56933
PHYSICAL	DENSITY	290	Kg/m <sup>3</sup>	± 20	UNE 56933
	HUMIDITY	5,5	%	± 1,5	UNE 56933
	RESIDUAL DUST	0,001	g/stopper	Max.	UNE 56923
	WATER ABSORPTION	10	% Δ weight	Max.	MI 98 IN CC
	CORK PERCENTAGE	75	%	Min.	T-IF-02
CHEMICAL	RESIDUAL PEROXIDE	0,2	mg/stopper	Max.	UNE 56929
	GLOBAL MIGRATION	10	mg/dm <sup>2</sup>	Max.	UNE-ISO 10106
MICROBIOLOGIC	BACTERIA	30	UFC/ stopper	Max.	UNE 56923
	MOLD AND YEAST	10	UFC/ stopper	Max.	UNE 56923
SPME/ GC/ MS ANALYSIS	2,4,6 –TCA,	1,9	ng/L	Max.	UNE 56930
	2,3,4,6 –TeCA, PCA ,Guayacol, Geosmina, Octanol, metilisoborneol, 2- isopropil-3metoxipirazina	< LD	ng/L	< LD	External
SENSORY	SENSORY DESVIATIONS	AQL 0.65. Method: water maceration.			

The products used for the manufacturing this product do not contain genetically modified organisms (GMOs) or allergens.

